

Page 1 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0029 Replacing version dated / version: 21.03.2019 / 0028 Valid from: 29.04.2020 PDF print date: 29.04.2020 Motorbike 2T-Additiv 250 mL Art.: 1582

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Motorbike 2T-Additiv 250 mL

Art.: 1582

അ

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Additives Uses advised against: No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
Classification according to Regulation (EC)1272/2008 (CLP)Hazard classHazard categoryHazard statementAsp. Tox.1H304-May be fatal if swallowed and enters airways.Aquatic Chronic3H412-Harmful to aquatic life with long lasting effects.

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 15

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0029 Replacing version dated / version: 21.03.2019 / 0028 Valid from: 29.04.2020 PDF print date: 29.04.2020 Motorbike 2T-Additiv 250 mL Art.: 1582



Danger

H304-May be fatal if swallowed and enters airways. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P301+P310+P331-IF SWALLOWED: Immediately call a POISON CENTER / doctor. Do NOT induce vomiting. P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics Hydrocarbons, C10, aromatics, >1% naphthalene Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3.2 Mixture

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	
EINECS, ELINCS, NLP	918-481-9 (REACH-IT List-No.)
CAS	
content %	80-<100
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Hydrocarbons, C10, aromatics, >1% naphthalene	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	919-284-0 (REACH-IT List-No.)
CAS	(64742-94-5)
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
	STOT SE 3, H336
	Aquatic Chronic 2, H411
Naphthalene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	601-052-00-2
EINECS, ELINCS, NLP	202-049-5



Page 3 of 15

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0029 Replacing version dated / version: 21.03.2019 / 0028 Valid from: 29.04.2020 PDF print date: 29.04.2020 Motorbike 2T-Additiv 250 mL Art.: 1582

CAS	91-20-3
content %	0,1-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP)	Carc. 2, H351
	Acute Tox. 4, H302
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Protective hand cream recommended.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately. Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur: Irritation of the eyes Irritation of the respiratory tract Headaches Dizziness Effects/damages the central nervous system Coordination disorders Unconsciousness Liver and kidney damage Blood count modifications Nausea Vomiting Danger of aspiration. Oedema of the lungs In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. 4.3 Indication of any immediate medical attention and special treatment needed

Ingestion: Activated carbon Gastric lavage (stomach washing) only under endotracheal intubation. Subsequent observation for pneumonia and pulmonary oedema.



Page 4 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0029 Replacing version dated / version: 21.03.2019 / 0028 Valid from: 29.04.2020 PDF print date: 29.04.2020 Motorbike 2T-Additiv 250 mL Art.: 1582

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO2 Extinction powder Foam Water jet spray

അ

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Hydrocarbons Toxic pyrolysis products. Explosive vapour/air or gas/air mixtures. Dangerous vapours heavier than air. In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke. Ensure sufficient supply of air. Avoid inhalation, and contact with eyes or skin. If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous. If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13. Ensure sufficient ventilation.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling 7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours. Keep away from sources of ignition - Do not smoke.

Do not heat to temperatures close to flash point.

Avoid contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.



Page 5 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0029 Replacing version dated / version: 21.03.2019 / 0028 Valid from: 29.04.2020 PDF print date: 29.04.2020 Motorbike 2T-Additiv 250 mL Art.: 1582

Observe directions on label and instructions for use. Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing. Not to be stored in gangways or stair wells. Solvent resistant floor Do not store with oxidizing agents. Store in a well ventilated place.

Protect from direct sunlight and warming.

7.3 Specific end use(s)

œ

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
WEL-TWA: 800 mg/m3	W	EL-STEL:						
Monitoring procedures:		ger - Hydrocarbons 2/a (81 0						
		ger - Hydrocarbons 0,1%/c (8	81 03 571)					
	- Com	our - KITA-187 S (551 174)						
BMGV:				(o RCP-method,		
			paragraphs	84-87, EH4	10)			
Chemical Name	Hydrocarbons, C10, ar	omatics, >1% naphthalene				Content %:1-<2,5		
WEL-TWA: 500 mg/m3 (Aromatics								
Monitoring procedures:		ger - Hydrocarbons 2/a (81 0						
		ger - Hydrocarbons 0,1%/c (8	81 03 571)					
	- Com	our - KITA-187 S (551 174)						
BMGV:			Other inform	nation:				
(B)						Content %:0,1-		
Chemical Name	Naphthalene					<0,25		
WEL-TWA: 500 mg/m3 (Aromatics	s) (WEL), 10 ppm 🛛 W	EL-STEL:				· · · · · · · · · · · · · · · · · · ·		
(50 mg/m3) (EU)								
Monitoring procedures:	- Com	our - KITA-153 U(C) (551 18						
BMGV:			Other inform	nation:				
Chemical Name	Hydrocarbons, C11-C1	4, n-alkanes, isoalkanes, cyc	clics, <2% aron	natics		Content %:		
WEL-TWA: 1200 mg/m3 (>=C7 nc	ormal and branched W	EL-STEL:						
chain alkanes)								
Monitoring procedures:		ger - Hydrocarbons 2/a (81 0						
		ger - Hydrocarbons 0,1%/c (8	81 03 571)					
	- Com	our - KITA-187 S (551 174)	-					
BMGV:			Other inform	nation:				
Naphthalene								
	osure route /	Effect on health	Descriptor	Value	Unit	Note		
Env	vironmental							
	npartment							
Env	ironment - freshwater		PNEC	2,4	µg/l			



Page 6 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0029 Replacing version dated / version: 21.03.2019 / 0028 Valid from: 29.04.2020 PDF print date: 29.04.2020 Motorbike 2T-Additiv 250 mL Art.: 1582

	Environment - marine		PNEC	0,24	µg/l
	Environment - sewage		PNEC	2,9	mg/l
	treatment plant				
	Environment - sediment,		PNEC	0,0672	mg/kg dry
	freshwater				weight
	Environment - sediment,		PNEC	0,0672	mg/kg dry
	marine				weight
	Environment - soil		PNEC	0,0533	mg/kg dry
					weight
Workers / employees	Human - dermal	Long term, systemic	DNEL	3,57	mg/kg
		effects			bw/day
Workers / employees	Human - inhalation	Long term, systemic	DNEL	25	mg/m3
		effects			
Workers / employees	Human - inhalation	Long term, local effects	DNEL	25	mg/m3

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

ആ

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Solvent resistant protective gloves (EN 374). If applicable Protective Viton® / fluoroelastomer gloves (EN 374). Permeation time (penetration time) in minutes: >480 Minimum layer thickness in mm: 0,4 Protective hand cream recommended. The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:



Page 7 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0029 Replacing version dated / version: 21.03.2019 / 0028 Valid from: 29.04.2020 PDF print date: 29.04.2020 Motorbike 2T-Additiv 250 mL Art.: 1582

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Gas mask filter A (EN 14387), code colour brown Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

ആ

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Dhusiaal atata	•
Physical state:	Liquid
Colour:	Light yellow
Colour:	Clear
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	145 °C
Flash point:	>61 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Vapours heavier than air.
Density:	0,765 g/ml (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	<7 mm2/s (40°C)
Explosive properties:	Product is not explosive. When using: development of explosive
· · ·	vapour/air mixture possible.
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity



Page 8 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0029 Replacing version dated / version: 21.03.2019 / 0028 Valid from: 29.04.2020 PDF print date: 29.04.2020 Motorbike 2T-Additiv 250 mL Art.: 1582

The product has not been tested. **10.2 Chemical stability**

œ

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Motorbike 21-Additiv 250 mL						
Art.: 1582						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						negative, the
						real
						Naphthalene
						content is <1%
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous	
					Toxicity)	conclusion	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	Analogous	
					Dermal Toxicity)	conclusion	
Acute toxicity, by inhalation:	LC50	>4951	mg/m3/4h	Rat	OECD 403 (Acute	Analogous	
					Inhalation Toxicity)	conclusion,	
						Vapours	
Skin corrosion/irritation:					OECD 404 (Acute	Not irritant,	
					Dermal	Analogous	
					Irritation/Corrosion)	conclusion	
Serious eye damage/irritation:					OECD 405 (Acute Eye	Not irritant,	
					Irritation/Corrosion)	Analogous	
						conclusion	
Respiratory or skin					OECD 406 (Skin	Not sensitizising,	
sensitisation:					Sensitisation)	Analogous	
						conclusion	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative,	
					Mammalian	Analogous	
					Chromosome	conclusion	
					Aberration Test)		



Page 9 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0029 Replacing version dated / version: 21.03.2019 / 0028 Valid from: 29.04.2020 PDF print date: 29.04.2020 Motorbike 2T-Additiv 250 mL Art.: 1582

œ.

Germ cell mutagenicity:		OECD 474 (Mammalian	Negative,
		Erythrocyte	Analogous
		Micronucleus Test)	conclusion
Germ cell mutagenicity:	Salmonella	OECD 471 (Bacterial	Negative
	typhimurium	Reverse Mutation Test)	
Carcinogenicity:		OECD 453 (Combined	Negative,
		Chronic	Analogous
		Toxicity/Carcinogenicity	conclusion
		Studies)	
Reproductive toxicity:		OECD 414 (Prenatal	Negative,
		Developmental Toxicity	Analogous
		Study)	conclusion
Specific target organ toxicity -		OECD 408 (Repeated	Negative,
repeated exposure (STOT-RE):		Dose 90-Day Oral	Analogous
		Toxicity Study in	conclusion
		Rodents)	
Aspiration hazard:			Yes
Symptoms:			unconsciousness
			, headaches,
			dizziness
Other information:			Repeated
			exposure may
			cause skin
			dryness or
			cracking.

Hydrocarbons, C10, aromatics, >1% naphthalene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	~7093	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>4688	mg/m3	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	490	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2500	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>110	mg/l/4h	Rat		Vapours
Symptoms:						lack of appetite, ataxia, breathing difficulties, unconsciousnes , diarrhoea, cornea opacity, headaches, cramps, gastrointestinal disturbances, mucous membrane irritation, dizziness, nausea and vomiting.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	



Page 10 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0029 Replacing version dated / version: 21.03.2019 / 0028 Valid from: 29.04.2020 PDF print date: 29.04.2020 Motorbike 2T-Additiv 250 mL Art.: 1582

œ

Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Analogous conclusion, Drying of the skin., Dermatitis (skin inflammation)
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Analogous conclusion, Slightly irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:					in vivo	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Analogous conclusion, Negative
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Analogous conclusion, Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						Analogous conclusion, No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Analogous conclusion, Not to be expected
Aspiration hazard:						Yes
Symptoms:						drying of the skin., headaches, fatigue, dizziness, nausea, diarrhoea, vomiting

SECTION 12: Ecological information

Motorbike 2T-Additiv 250 mL							
Art.: 1582							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							Isolate as much
degradability:							as possible with
							an oil separator.
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.



Page 11 of 15 Safety data sheet accordir Revision date / version: 29 Replacing version dated / Valid from: 29.04.2020	9.04.2020 / 002 version: 21.03.	29		nex II			
PDF print date: 29.04.202 Motorbike 2T-Additiv 250 Art.: 1582							
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.
Hydrocarbons, C10-C13,							
Toxicity / effect 12.5. Results of PBT	Endpoint	Time	Value	Unit	Organism	Test method	Notes No PBT
Water solubility:							substance, No vPvB substance Product floats o the water
12.1. Toxicity to fish:	LL50	96h	>1000	ma/l	Opeorbyrochup	OECD 203 (Fish,	surface.
				mg/l	Oncorhynchus mykiss	Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna	Test)	
12.2. Persistence and degradability:		28d	80	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymen pyriformis		
Hydrocarbons, C10, aroı	natics >1% na	nhthalono					
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	EL50	48h	10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EL50	72h	>1-<3	mg/l	Raphidocelis subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Naphthalene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1,99	mg/l	Pimephales promelas		Does not conform with El classification.
12.1. Toxicity to fish:	LC50	96h	0,51	mg/l	Denkala		
12.1. Toxicity to daphnia: 12.1. Toxicity to algae:	EC50 LC50	48h 4h	2,19 2,96	mg/l mg/l	Daphnia magna Selenastrum capricornutum		
,,,,	BCF		>100				Low
12.3. Bioaccumulative potential:							
12.3. Bioaccumulative potential: Other information:	BOD5		0	%			
12.3. Bioaccumulative potential: Other information: Other information: Other information:			0 22 3,3	%			



Page 12 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0029 Replacing version dated / version: 21.03.2019 / 0028 Valid from: 29.04.2020 PDF print date: 29.04.2020 Motorbike 2T-Additiv 250 mL Art.: 1582

œ

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,17	mg/l	Oncorhynchus	QSAR	
-				_	mykiss		
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	NOELR	21d	1,22	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
12.2. Persistence and		28d	69	%		OECD 301 F	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Manometric	
						Respirometry Test)	
12.3. Bioaccumulative	Log Pow		6-8				High
potential:							
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 07 04 other organic solvents, washing liquids and mother liquors

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements	
14.1. UN number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable



- (B)										
Page 13 of 15										
Safety data sheet according to Regulation (EC) No 19	907/2006, Annex II									
Revision date / version: 29.04.2020 / 0029 Replacing version dated / version: 21.03.2019 / 0028 Valid from: 29.04.2020 PDF print date: 29.04.2020										
						Motorbike 2T-Additiv 250 mL				
						Art.: 1582				
						Tunnel restriction code:				
Transport by sea (IMDG-code)										
14.2. UN proper shipping name:										
14.3. Transport hazard class(es):	n.a.									
14.4. Packing group:	n.a.									
Marine Pollutant:	n.a									
14.5. Environmental hazards:	Not applicable									
Transport by air (IATA)										
14.2. UN proper shipping name:										
14.3. Transport hazard class(es):	n.a.									
14.4. Packing group:	n.a.									
14.5. Environmental hazards:	Not applicable									
14.6. Special precautions for user										
Unless specified otherwise, general measures for safe	e transport must be followed.									
14.7. Transport in bulk according to	Annex II of MARPOL and the IBC Code									
Non-dangerous material according to Transport Regu										
SECTI	ON 15: Regulatory information									

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): Directive 2010/75/EU (VOC):

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

1

~ 96 %

~ 764,1 g/l

Revised sections: These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Asp. Tox. — Aspiration hazard Aquatic Chronic — Hazardous to the aquatic environment - chronic STOT SE — Specific target organ toxicity - single exposure - narcotic effects



Page 14 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0029 Replacing version dated / version: 21.03.2019 / 0028 Valid from: 29.04.2020 PDF print date: 29.04.2020 Motorbike 2T-Additiv 250 mL Art.: 1582

Carc. — Carcinogenicity Acute Tox. — Acute toxicity - oral Aquatic Acute — Hazardous to the aquatic environment - acute

ആ

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) Adsorbable organic halogen compounds AOX approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germanv) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BSEF The International Bromine Council body weight bw CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level dw dry weight e.g. for example (abbreviation of Latin 'exempli gratia'), for instance European Community EC ECHA European Chemicals Agency European Economic Community FFC EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances ΕN European Norms EPA United States Environmental Protection Agency (United States of America) etc. et cetera ΕU **European Union** EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) International Maritime Code for Dangerous Goods IMDG-code including, inclusive incl. IUCLID International Uniform Chemical Information Database LQ Limited Quantities International Convention for the Prevention of Marine Pollution from Ships MARPOL not applicable n.a. n.av. not available not checked n.c. n.d.a. no data available OECD Organisation for Economic Co-operation and Development org. organic PBT persistent, bioaccumulative and toxic PE Polyethylene PNEC Predicted No Effect Concentration mag parts per million Polyvinylchloride PVC REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) **REACH-IT List-No.** 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.



Page 15 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.04.2020 / 0029 Replacing version dated / version: 21.03.2019 / 0028 Valid from: 29.04.2020 PDF print date: 29.04.2020 Motorbike 2T-Additiv 250 mL Art.: 1582

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

GB

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

 $\ensuremath{\mathbb{C}}$ by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.